



# PT TIMURAYA TUNGGAL

Perkantoran Permata Senayan D-35, Jl. TentaraPelajar, Jakarta-12210, Indonesia

Tel : (62-21) 5794 0809

Fax : (62-21) 5794 0810

e-mail : contact@timuraya.com

Website : www.timuraya.com

## Product Information Sheet | PIS | Aluminum Sulfate – Technical Grade



### Product Identification

<b>Product Name</b>	<b>Aluminum Sulfate</b>
<b>Chemical Name</b>	Aluminum Sulfate
<b>Synonym</b>	Alum, Aluminum alum
<b>Registrations</b>	CAS-Nr. 7784-31-8(Hydrate) EC-Nr. 233-135-0 U.N. 8207
<b>Appearance</b>	White to brownish solid Yellow to brownish liquid

### Packing

<b>Size Solid</b>	Granular standard, powder granular special grade (1-3) mm ; (1-12) mm Multiply kraft paper bag PE inner linner PP woven bag with PE inner liner PP jumbo / big bag with PE laminated
<b>25 kg</b>	
<b>25 kg or 50 kg</b>	
<b>500 kg to 1000 kg net in</b>	
<b>Size Liquid</b>	In tank car
<b>10 - 20 ton</b>	

### Applications

- Water Purification
- Sewage Treatment
- Water Proofing Agent for concrete
- Sizing Paper and pH Control
- Clarifying Agent for Fats and Oil
- Deodorizer and Decolorizer in Petroleum Refinery Processes

Product Specifications		Granular			Powder	Liquid
		Standard	Special Grade			
		< 12 mm	(1-3) mm	(1-12) mm		
Particle Size	Unit %	< 12 mm 98% min	(1-3) mm 85% min	(1-12) mm 90% min	< 2 mm 98% min	
Bulk Density	g/cm <sup>3</sup>	0.83-0.87	0.84-0.89	0.83-0.87	0.90-0.93	
Specific Gravity (20°C)	g/cm <sup>3</sup>					1.3 min
Aluminum Oxide (Al <sub>2</sub> O <sub>3</sub> )	%	17 min				8 min
Water insoluble Matter	%	0.5 max				0.25 max
Iron (Fe)	%	0.01 max				0.01 max
Heavy metal (as Pb)	%	0.0010 max				0.0010 max
Arsenic (As)	%	0.0002 max				0.0002 max
pH 1 % solution (solid)		3.0 min				
pH 2 % solution (liquid)						3.0 min

Testing method:

- Singapore Standard 36 : 1971
- SNI 0032-2011 - Solid & liquid